



HUGO 2600 1D Laser Omni-directional Barcode Scanner

Interface	USB HID KEYBOARD/RS-232	Mechanical shock	1.2m drop onto concrete surface
Voltage requirement	DC 5V±10%	Temp	-10° to 50°C / 14° to 122°F(operation) -20° to 60°C / -4° to 140°F(storage)
Current consumption	Max:270mA	Humidity	5 - 90% (operation) 5 - 90% (storage))
Light source	650nm visible laser diode	Ambient Light	Fluorescent light: 4000 lx max Direct sun light: 80,000 lx max White light: 4000 lx max
Scan line	20 lines	Decode capability	1D : UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128, Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, MSI/Plessey, China Postal Code, Code 32 (Italian Pharmacode), RSS 14, RSS Limited, RSS Expanded
Scan rate	1400(scans/second)	Laser Safety	CDRHII;IEC 60825-1:2
Decode angle	5 directions of scan field	Environmental	RoHS
Min resolution	0.127mm/5mil(PCS 0.9)	Dimensions	160mm x 100mm x 100mm(L*W*H)
Min .PCS value	>30%UPC/EAN 13(13mil)	Weight	352g
Curvature	R≥15 mm(EAN8),R≥20 mm(EAN13) (resolution=0.26mm(PCS=0.9)		
Compatibility	Win OS / Mac OS/ Linux Android/IOS/Embedded OS		

*The appearance and specification of the product would be changed without prior notice in order to improve it

VIETNAM HTMART TECHNOLOGY CO.,LTD

Add: No 26, lane 188, Vuong Thua Vu street, Thanh Xuan district, Hanoi Capital, Vietnam

Tell: +84466568678 Website: www.thietbibanhang.net

Contact: Ms. TRANG TRAN (Sales Director) Mobile: +84975174204

Skype: trang_215 Email: htmartinfo@gmail.com